

CLOSE

PRODUCT FOCUS: Moisture Control

Moisture Control



GUARANTEED R-VALUE

Foam-Control Plus+ architectural grade EPS insulation has added face stamping and pre-scoring and now warrants 100% of its R-value for 50 years—an industry first. Regardless of thickness, density or application, the warranty is the same. Foam-Control Plus+ is available in R-Values of R-5, R-7.5, R-10, R-15, R-20 and R-30. Circle 439

ACH Foam Technologies
www.achfoam.com



EFFICIENT FOAM

The HD Composite panel is a closed-cell, extremely lightweight and resilient EPS foam factory bonded to high-density polyisocyanurate cover board. The factory-laminated composite insulation provides significant field labor savings, a cover board offering high compressive strength (100 psi) and high thermal efficiency that is not available with traditional foam insulation. HD Composite insulation can be used to achieve UL Class A fire ratings on combustible roof decks without the use of gypsum or other cover boards. The product is available in standard 4-ft. x 8-ft. panels, with thicknesses ranging from 1.5 in. to 7 in. Custom lengths and widths are also available. Circle 438

InsulFoam
www.insulfoam.com



MITIGATING MOISTURE

EcoBay CC closed-cell spray-applied polyurethane foam insulation is produced from a two component, HFC-245fa blown, medium-density structural system designed for commercial applications. The foam forms an integral part of any air barrier system and is made with an "A" component or aromatic diisocyanate and a blended "B" component, which includes polyols, fire-retarding materials and additives. It yields a high R-value and it mitigates thermal shorts when applied as continuous insulation along the perimeter of a structure. The foam is available in two grades for warm and cold weather applications. Circle 437

Bayer MaterialScience
materials.science.bayer.com